

TRIPOD SYSTEMS

7 ft. (2.10m) Tripod with 60 ft. (18.2 m) Winch

DXFP421300-007

BENEFITS AND FEATURES

The DEWALT 7 ft. (2.13 m) Adjustable Tripod with bag and DEWALT 60 ft. (18.2 m) Winch provides a portable Fall Protection and Access system for vertical entry/egress into confined spaces. Weighing only 93 lbs. (42 kg) the DEWALT 7 ft. (2.13 m) Adjustable legs for easy transportation and installation purposes anchor point for fall protection and rescue applications.

FLEXIBILITY: Adjustable Tripod folds down to 63 in. (1.6 m) length for easy storage and transport. No tools are required for assembly. Dual pulleys built into the tripod head for winch/SRL lifeline. Includes 1 pre-installed Winch or Retrieval SRL Mounting bracket.

DURABILITY: Built with high strength aluminum alloy, the DEWALT Tripod System components are designed to ensure longevity, even in the toughest conditions.



60 ft. (18.2 m) Winch

SPECIFICATIONS

Maximum Breaking Strength: 5,000 lbs. (23 kN)

Fall Arrest Capacity: 310 lbs. (141 kg) OSHA 420 lbs. (190 kg) 1 user.

Rescue Capacity: 620 lbs. (280 kg) 2 users.

Min Height: 48 in. (1.2 m) with 25 in. (0.6 m) hole clearance

Max Height: 89 in. (2.2 m) with 46 in. (1.1 m) hole clearance

Material: (Head) Prime quality aluminum alloy. ED Coated black (Finish)
 (Locking Pins) Prime quality aluminum alloy eye bolt & stainless steel.
 Deburred & Polished (Finish)
 (Legs) Prime quality aluminum alloy. Anodized (Finish)

RELEVANT STANDARDS

Tripod: ANSI Z359.18-2017 Type A - Winch: ANSI Z359.4 - 2013 - OSHA 1926.502 and 1910.66

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY