

# DAVIT SYSTEM

5 Piece Davit System, 54 in. (1.37 m) Mast with 60 ft. (18.2 m) Winch and 60 ft. (18.2 m) Retrieval SRL

**DXFP451919-054**

## BENEFITS AND FEATURES

The DEWALT 5 Piece Davit System with 54 in. (1.37 m) mast, with a 60 ft. (18.2 m) Winch and 60 ft. (18.2 m) Retrieval SRL, provides a portable Fall Protection and Access system for vertical entry/egress into confined spaces.

**DURABILITY:** Built with high strength aluminum alloy, the DEWALT Davit System components are designed to ensure longevity, even in the toughest conditions.

**FLEXIBILITY:** The DEWALT Davit System breaks down into five components for easy storage, transport and setup. No tools are required for assembly. Includes pre-installed Winch and Retrieval SRL Mounting brackets. Removable legs for easy transportation and installation purpose. Multiple anchorage points for fall protection and rescue applications. Built-in swivel feature allows the davit column assembly to be rotated up to 360°.

## SPECIFICATIONS

**Maximum Breaking Strength:** 5,000 lbs. (23 kN)

**Capacity:** 310 lbs. (141 kg) OSHA 620 lbs. (282 kg) for Rescue

**Max Height:** 72 in. (1.8 m)

**Weight:** 264.7 lbs. 120 kg

**Working Width:** 43 in. (1.1 m) to 59 in. (1.5 m)

**Material:** High Strength Aluminum Alloy



**ADJUSTABILITY:** Davit System Boom comes with 3 adjustment positions for the user to adjust the height to meet various situations: Min. Height: 65 in. (1.58 m) with 36 in. (0.91 m) offset. Middle Height: 79 in. (2.0 m) with 33 in. (0.84 m) offset. Max. Height: 90 in. (2.3 m) with 26 in. (0.66 m) offset.

## RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type A - OSHA 1926.502 and 1910.66

## WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

## WARRANTY

**2 YEAR LIMITED WARRANTY**