

D1000 HARNESSES

5 Points Adjustment with Pass-Thru Legs Buckles

DXFP512001

BENEFITS AND FEATURES

The DEWALT D1000 Full Body Harness provides everything you need to ensure compliance and maximum safety when working at height. It features 5 points of adjustment, pass-through chest, and leg attachments, lanyard keepers. The heavy-duty polyester repellent webbing resists oil, water, and stains to help ensure ease of maintenance throughout its service life.

QUICK HARNES CONNECTIONS: The pass-through buckles provide a quick and easy fit when donning the harness.

CONVENIENT LANYARD STORAGE: Two lanyard keepers to safely park unused lanyard leg.

EASY FALL DETECTION: Impact indicators to easily identify if a fall has occurred.



SPECIFICATIONS

Webbing Polyester: 5,000 lbs. (2267 KG.) min. static strength

Weight Rating: Harness rated to 310 lbs. (141 kg)

Buckles and Adjusters: Plated alloy steel

Materials of construction: Repellent Webbing Polyester

RELEVANT STANDARDS

Meets ANSI Z359.11, OSHA 1910.66, OSHA 1926.504

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

6 Ft. [1.8M.] LANYARD

Internal Energy Absorbing Lanyard

DXFP612111

BENEFITS AND FEATURES

The DEWALT internal energy absorbing lanyard provides everything you need to ensure compliance and maximum safety when working at height. It features a one-piece lanyard with an internal energy absorber, durable polyester webbing, and plated-steel snap-hooks, with 3,600 lbs. (16kN) gated hooks., ANSI-approved gates. An excellent choice for a variety of worksites.

LIGHTWEIGHT DESIGN: Built-in energy absorber reduces weight over external shock pack designs.

DURABILITY: Plated steel hardware and Polyester webbing for extended life and durability.

SAFETY ALERTS: Built in fall indicator lets you know when a fall has occurred, and lanyard should be removed from service.

SPECIFICATIONS

Length: 6 Ft. [1.8 m.]

ANSI Compliant: 3,600 lbs. (16kN) gated hooks.

Materials of construction: Polyester, Steel

Net Weight in Lbs. (Product): 3.2

RELEVANT STANDARDS

Meets ANSI Z359.13, OSHA 1910.66, OSHA 1926.502

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

