

VERTICAL LIFELINE WITH ROPE ADJUSTER

Integral 2 Ft. [0.6M.] Energy Absorber Lanyard

DXFP210050

BENEFITS AND FEATURES

The DEWALT 50 ft. Vertical Lifeline with Rope Adjuster is designed as a key component for roof-top safety. The rope is water and abrasion resistant for strength and durability, while the built-in rope adjuster provides the versatility of free movement or fixing in place for fall restraint. When used with a DEWALT roof-top anchor and harness it becomes an integral piece in a personal fall arrest system.

ABRASION RESISTANT: Polysteel rope resists abrasion and water for longer life.

STRENGTH & DURABILITY: Alloy steel hardware with zinc plating for high strength and long life.

EASE OF MOVEMENT: Manual positioning device allows for smooth movement around working surface.

SPECIFICATIONS

Length: 50 Ft. [15 m.]

Worker Capacity Range: 130-310 lbs.(58-140 kg)

Min. Breaking Strength: 5,000 lbs.(2267 kg)

Materials of construction: Poly Steel Rope, alloy steel, polyester

Net Weight in Lbs. (Product): 8.2

RELEVANT STANDARDS

Meets ANSI Z359.1, OSHA 1910.66, OSHA 1926.502

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY



D1000 HARNESSES

5 Points Adjustment with Pass-Thru Legs Buckles

DXFP512001

BENEFITS AND FEATURES

The DEWALT D1000 Full Body Harness provides everything you need to ensure compliance and maximum safety when working at height. It features 5 points of adjustment, pass-through chest, and leg attachments, lanyard keepers. The heavy-duty polyester repellent webbing resists oil, water, and stains to help ensure ease of maintenance throughout its service life.

QUICK HARNES CONNECTIONS: The pass-through buckles provide a quick and easy fit when donning the harness.

CONVENIENT LANYARD STORAGE: Two lanyard keepers to safely park unused lanyard leg.

EASY FALL DETECTION: Impact indicators to easily identify if a fall has occurred.



SPECIFICATIONS

Webbing Polyester: 5,000 lbs. (2267 KG.) min. static strength

Weight Rating: Harness rated to 310 lbs. (141 kg)

Buckles and Adjusters: Plated alloy steel

Materials of construction: Repellent Webbing Polyester

RELEVANT STANDARDS

Meets ANSI Z359.11, OSHA 1910.66, OSHA 1926.504

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

REUSABLE ROOFTOP ANCHOR

Hinged Steel Anchor

DXFP842001

BENEFITS AND FEATURES

The DEWALT Reusable Roof Anchor is designed for use on wood, structures. The hinged design allows it to work on nearly all roof pitches. The anchor is made of coated steel for longer lasting product life. It can be installed with either screws or nails (depending on roof pitch), and comes with both nails and a QTY 12 # 12x2" hex head fasteners.

REUSABLE DESIGN: Designed for multiple use with new fasteners.

VERSATILITY: Hinged design allows anchor to adapt to varying roof pitches and comes with both nails and screws for easy installation.

DURABILITY: Plated steel construction, powder coated high strength and durability.



SPECIFICATIONS

Total Length: 20.47 in. [52 cm.]

Worker Capacity Range: 130-420 lbs. (58-190 kg)

Min. Breaking Strength: 5,000 lbs.(2267 kg)

Materials of construction: Powder coated steel

Net Weight in Lbs. (Product): 2.4

RELEVANT STANDARDS

Meets ANSI Z359.1, OSHA 1910.66, OSHA 1926.502

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY