

# TAPE MEASURE HOLDER

DXDP610200



## BENEFITS AND FEATURES

The DEWALT Tape measure holder adjusts to fit most tape measures up to 35 Ft. (10.67 M.). The steel D-ring allows the quick connection of a tool lanyard to the holder to protect workers and property below from damage. The stainless clip allows the holder to be easily attached to harnesses and work belts.

**VERSATILITY:** Hook and loop closures allow for the fit of most tape measures up to 35 feet (10.67 meters)

**SECURE CONNECTION:** Hook and loop closures and elastic straps allow for secure and safe fit.

**DURABILITY:** Rugged polyester material and steel d-ring for durability and longer life.

## SPECIFICATIONS

**Dimensions:** H 5.11 W 3.74 in. (13 x 95 cm)

**Net Weight in lbs (Product):** 0.286 (0.13 Kg)

**Maximum safe working capacity:** 2 lbs (0.9 kg)

**Materials of construction:** Polyester and steel

## RELEVANT STANDARDS

Meets ANSI/ISEA 121-2018 standard

## WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

## WARRANTY

2 YEAR LIMITED WARRANTY

# QUICK CONNECT TOOL LANYARD W/ATTACHMENT

DXDP710501



## BENEFITS AND FEATURES

The DEWALT shock absorbing tool lanyard with a carabiner on one end and a detachable elastic loop on the other end. Allows for quick connection and exchange of small tools weighing 5lbs. (2.3 Kg) or less. Once connected, it becomes a key component to a tethering system intended to prevent accidental drops that can lead to injuries and property damage.

**SECURITY:** Captive eye, dual-action, locking carabiner for worry free operation

**FLEXIBILITY:** Elastic, bungee style webbing provides a wide working range

**LIGHTWEIGHT:** Aluminum carabiner provides less weight than steel connections

## SPECIFICATIONS

Relaxed length: 37 in. (93 cm)

Extended length: 51 in. (129 cm)

Maximum safe working capacity: 5 lbs (2.3 kg)

Materials of construction: Polyester and aluminum

## RELEVANT STANDARDS

Meets ANSI/ISEA 121-2018 standard

## WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

## WARRANTY

2 YEAR LIMITED WARRANTY