

D1000 HARNESS

Vest Style, 5 Points Adjustment with Pass-Thru Legs Buckles

DXFP512001(U) Size: Universal

BENEFITS AND FEATURES

The DEWALT D1000 Full Body Harness provides an exceptional range of features at a surprisingly affordable price. The harness has 5 points of adjustment, pass-through chest and tongue buckle leg connections, lanyard keepers, and heavy-duty, repellent polyester webbing. Some models come with a removable shoulder pad included for added comfort.

DURABILITY: Polyester webbing with repellent coating resists stains from oil and water.

QUICK HARNESS CONNECTIONS: The pass-through buckles provide a quick and easy fit when donning the harness.

CONVENIENT LANYARD STORAGE: Two lanyard keepers to safely park unused lanyard leg.

VERSATILITY: The quick connect SRL adapter allows for fast installation of your SRL while leaving the D-Ring free for lanyards and rescue device connections



Webbing Polyester: 5,000 lbs. (2267 KG.) min. static strength
Weight Rating: ANSI 310 lbs. (141 kg) - OSHA 420 lbs (191 kg)

Buckles and Adjusters: Plated alloy steel

Materials of construction: Repellent Webbing Polyester

RELEVANT STANDARDS

Meets ANSI Z359.11-21, OSHA 1910.140, OSHA 1926.502

WARNINGS

- ·Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- ·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY



EASE OF INSPECTION RFID & QR CODE TAG





ASSETS MANAGEMENT INSPECTION APPLICATION



6 Ft. [1.8M.] SINGLE LEG LANYARD

Internal Absorber, with Steel Snaphooks on both ends

DXFP612111

BENEFITS AND FEATURES

The DEWALT internal energy absorbing lanyards come in a variety of styles and configurations to fit the requirements of most work situations. Available in single & twin leg, with steel & aluminum connectors.

LIGHTWEIGHT: Internal energy absorber helps reduce weight and bulk of most external absorbers.

EASE OF INSPECTION: All DEWALT lanyards come with a QR code and RFID tag for quick scan and registration into an asset management / inspection application.

LABEL PROTECTION: ALL DEWALT Lanyards comes with a protected label pack to prevent labels from being damaged by tough conditions.

EASY FALL ALERT: All DEWALT lanyards come with an integrated impact indicator to show users when the device has seen a fall and should be removed from service.



SPECIFICATIONS

Length: 6 Ft. [1.8 m.]

ANSI Compliant: 3,600 lbs. (16kN) gated hooks.

Breaking Strength: 6,000 lbs. (2721) kg.

Materials of construction: Polyester, Steel

RELEVANT STANDARDS

Meets ANSI Z359.13.2013, OSHA 1910.140, OSHA 1926.502

WARNINGS

- ·Read, understand and follow all labels and instructions prior to use.
- ·Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

EASE OF INSPECTION RFID & QR CODE TAG





ASSETS MANAGEMENT INSPECTION APPLICATION