

# SAFETY KIT

## Fall Protection Rooftop Safety Kit

DXFP110050

### BENEFITS AND FEATURES

The DEWALT® Fall Protection Rooftop Safety Kit offers a complete setup for working at height applications. It includes our D1000 harness with 5 pts of adjustment and pass-through chest and Tongue buckle legs connections, a 50 ft. (7.6 m) Internal Energy Absorber lifeline, and a Reusable Rooftop Anchor. It all comes in a convenient bucket, for easy transportation and storage.

### SPECIFICATIONS

#### DXFP512001

D1000 Vest Style Harness, 5 point adjustment with Pass-Through chest, PT legs connections.

**Webbing Polyester:** 5,000 lbs. / 2267 kg Min. Static Strength

**Buckles and Adjusters:** Plated Alloy Steel

**Weight Capacity:** OSHA 420 lbs. /191 kg - ANSI 310 lbs. / 140 kg

**Meets:** ANSI Z359.11-2021, OSHA 1910.140, OSHA 1926.502

CAN/GSA Z259.10-18

#### DXFP210050

50 ft. (7.6 m) Lifeline with an integrated energy absorber Lifeline.

**Connector Anchor End:** 3,600 lbs. (16 kN) Gate Steel Snap Hook

**Harness Connector:** 3,600 lbs. (16 kN) Gate Steel Snap Hook

**Rope Diameter:** 5/8 in. (1.58 cm)

**Maximum Breaking Strength:** 5,000 lbs. (23 kN)

**Material:** Polyester, Steel

**Weight Capacity:** ANSI 310 lbs. / 140 kg

**Meets:** ANSI Z359.1-2007, OSHA 1926.502, OSHA 1910.66

CAN/GSA Z259.2.5-17 (R2021)

#### DXFP842001

Reusable Rooftop Anchor, coated steel, Fastners and Nails included

**Maximum Breaking Strength:** 5,000 lbs. (23 kN)

**Material:** Coated Steel

**Weight Capacity:** ANSI 310 lbs. / 140 kg

**Meets:** ANSI Z359.18-2017 Type A, OSHA 1926.502, OSHA 1910.66

CAN/GSA Z259.15-22

### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

### WARRANTY

2 YEAR LIMITED WARRANTY

