

HORIZONTAL LIFELINE

Horizontal Lifeline System - Rope - Temporary - 2 Person - 100 Ft. (30.5 M.)

DXFP160020

BENEFITS AND FEATURES

The DEWALT 2-Person Temporary Horizontal Lifeline is lightweight, easy to install and adjustable between 15 ft. (4.6m) and 100 ft. (30.5m). Made of 5/8in. (16mm) kernmantle rope, it includes installation carabiner at each end, tension indicator, fall/impact indicator, and (2) 6 ft. (1.8 m) anchor straps.

DURABILITY: The high strength 5/8 in. (16mm) kern-mantle rope provides excellent wear resistance while the aluminum and stainless steel tensioner provides excellent weather resistance.

COMPACT & LIGHTWEIGHT: Weighing only 18.2 lbs (8.2 Kg.), this temporary horizontal lifeline is easily moved and reused from location to location.

FLEXIBILITY: Can be used for 1 to 2 users and the included web anchor straps allow for use on most vertical beams or posts.



SPECIFICATIONS

Maximum Breaking Strength: 5600 lbs. (25 kN.)

Capacity: 2 Users, 310 lbs. (141 kg) Each

Size: Span length of 15 ft.(4.6 m.) to 100 ft. (30.5 m.)

Total Weight: 18.2 lbs. (8.26 Kg.) Entire System

Material: O-Rings (Forged Alloy Steel)-**Tensioner:** High Strength Alloy Steel-**Lifeline:** 5/8 in.(16mm.) Kernmantle Rope

RELEVANT STANDARDS

Meets OSHA 1910.66, OSHA 1926.502

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY