

# SELF RETRACTING LIFELINE

## D200 SRL -Leading Edge - Galvanized Steel Cable - 25 ft. (7.62 m)

### DXFP210221-025

#### BENEFITS AND FEATURES

The DEWALT 25 ft. (7.62 m) anchor mounted leading edge SRL with energy absorber at harness end provides users with a dependable, versatile and rugged fall protection anchor mounted connector that can be mounted at foot-level or above for a wide variety of applications.

**STRENGTH:** Rated OSHA & ANSI, the DEWALT D200 LE is an exceptional fall protection connector and reduces free fall and arrest forces on the body.

**FLEXIBILITY:** The DEWALT D200 LE provides a trip-free connector experience while allowing ease of movement.

**DURABILITY:** The rugged high impact strength polymer housing with recessed labels ensures longevity, even in the toughest conditions and the 7/32 in. (5.56 mm) galvanized cable provides protection from sharp edges.

#### SPECIFICATIONS

**CONNECTOR ANCHOR END:** 3,600 lbs. (16kN) gate Steel (galvanized alloy steel with golden yellow/silver passivation) Carabiner

**HARNESS CONNECTOR:** 3,600 lbs. (16kN) gate Steel (galvanized alloy steel with golden yellow/silver passivation) Carabiner

**Unit Weight:** 12.9 lbs. (5.87 kg)

#### Material:

Casing: High Impact Strength Polymer

Lifeline: Galvanized Steel Cable 7/32 in. (5.56 mm)

#### RELEVANT STANDARDS

Meets ANSI Z359.14-2021, OSHA 1926.502 and 1910.66

#### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

#### WARRANTY

2 YEAR LIMITED WARRANTY

