DEWALT FALL PROTECTION

CLASS 1 PERSONAL

SELF RETRACTING LIFELINE

SELF RETRACTING LIFELINE

D100P Personal SRL - Single - Aluminum Carabiner

DXFP242411-006



BENEFITS AND FEATURES

The DEWALT 6 ft. (1.8 m) single personal SRL with aluminum carabiner at anchor end provides users with a lightweight, versatile and rugged fall protection connector for a wide variety of applications.

STRENGTH: Rated OSHA & ANSI, the DEWALT D100P is an exceptional fall protection connector and reduces free fall and arrest forces on the body.

FLEXIBILITY: The DEWALT D100P Single unit provides a trip-free connector experience while allowing ease of movement.

DURABILITY: The rugged high impact strength polymer housing with recessed labels ensures longevity, even in the toughest conditions.

SPECIFICATIONS

CONNECTOR ANCHOR END: 3,600 lbs. (16kN) gate Aluminum (High strength aluminum alloy) Carabiner

HARNESS CONNECTOR: 3,600 lbs. (16kN) gate Steel (galvanized alloy steel with silver passivation) Carabiner

Unit Weight: 2.44 lbs. (1.11 kg)

Material:
Casing: High Impact Strength Polymer
Lifeline: Dyneema webbing 13/16 in. (20.6 mm)

OSHA CAPACITY MAX 420 lbs 190 kg/

ANSI Z.359 14-2021
310 lbs / 140 kg ™

RELEVANT STANDARDS

Meets ANSI Z359.14-2021, OSHA 1926.502 and 1910.66

WARNINGS

·Read, understand and follow all labels and instructions prior to use.
·Inspect before each use.
·Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

2026 DEWALT. DEWALT® and GUARANTEED TOUGH® are registered trademarks of DEWALT Industrial Tool Co. and used under license by DEWALT Fall Protection. All rights reserved. The yellow and black color scheme is a trademark for DEWALT power tool and accessories. A licensee of DEWALT Industrial Tool Co. www.dewalt.com Trademark Licensee: DFP Safety Corp. 20711 Holt Av. Suite 1525 Lakeville, MN 55044 www.dfpsafety.com