

# D3000 HARNESS

Welding Vest Style, 5-Point, Back D-Rings, QC Chest, TB Legs

DXFP537011(XL-2XL)

Size: XL-2XL

## BENEFITS AND FEATURES

All DEWALT D3000 welding harnesses are constructed using Aramid FR webbing for use in high heat environments. The webbing is an excellent choice to resist splatter and burns from welding slag. The harnesses come in four sizes, belted and non-belted and include tongue buckle or quick connect buckle connections, giving you several options for the right fit to your job.

**FLAME RESISTANT:** Aramid FR webbing allows harness to be used in welding and other high heat applications.

**CONVENIENT LANYARD STORAGE:** resettable lanyard keepers to safely park unused lanyard leg.

**VERSATILITY:** The quick connect SRL adapter allows for fast installation of your SRL while leaving the D-Ring free for lanyards and rescue device connections.



## SPECIFICATIONS

**Aramid FR Webbing:** 5,000 lbs. (2267 KG.) min. static strength

**Weight Rating:** ANSI 310 lbs. (141 kg) - OSHA 420 lbs (191 kg)

**Buckles and Adjusters:** Plated alloy steel

**Materials of construction:** Aramid FR Webbing

## RELEVANT STANDARDS

Meets ANSI Z359.11-21, OSHA 1910.140, OSHA 1926.502

## WARNINGS


- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

## WARRANTY

2 YEAR LIMITED WARRANTY

EASE OF INSPECTION

RFID & QR CODE TAG



ASSETS MANAGEMENT  
INSPECTION APPLICATION