

6 Ft. [1.8M.] SINGLE LEG LANYARD

External Absorber, with Steel Snaphooks on D-Ring End and Steel Rebar Hook on Anchor End

DXFP611110 BENEFITS AND FEATURES

The DEWALT external energy absorbing lanyards come in a variety of styles and configurations to fit the requirements of most work situations. Available in single & twin leg, with steel & aluminum connectors.

LIGHTWEIGHT: Small energy absorber design reduces bulk and weight.

EASE OF INSPECTION: All DEWALT lanyards come with a QR code and RFID tag for quick scan and registration into an asset management / inspection application.

LABEL PROTECTION: All DEWALT Lanyards comes with a protected label pack to prevent labels from being damaged by tough conditions.

EASY FALL ALERT: All DEWALT lanyards come with an integrated impact indicator to show users when the device has seen a fall and should be removed from service.

SPECIFICATIONS

Length: 6 Ft. [1.8 m.]

ANSI Compliant: 3,600 lbs. (16kN) gated hooks.

Breaking Strength: 6,000 lbs. (2721) kg.

Materials of construction: Polyester, Steel

RELEVANT STANDARDS

Meets ANSI Z359.13.2013, OSHA 1910.140, OSHA 1926.502

WARNINGS

Read, understand and follow all labels and instructions prior to use.

Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY



EASE OF INSPECTION

RFID & QR CODE TAG



ASSETS MANAGEMENT INSPECTION APPLICATION