

6 Ft. [1.8M.] TWIN LEG LANYARD

External Absorber, with Steel Snaphooks on D-Ring End and Steel Rebar Hooks on Anchor End

DXFP611130

BENEFITS AND FEATURES

The DEWALT external energy absorbing lanyards come in a variety of styles and configurations to fit the requirements of most work situations. Available in single & twin leg, with steel & aluminum connectors.

LIGHTWEIGHT: Small energy absorber design reduces bulk and weight.

EASE OF INSPECTION: All DEWALT lanyards come with a QR code and RFID tag for quick scan and registration into an asset management / inspection application.

LABEL PROTECTION: ALL DEWALT Lanyards comes with a protected label pack to prevent labels from being damaged by tough conditions.

EASY FALL ALERT: All DEWALT lanyards come with an integrated impact indicator to show users when the device has seen a fall and should be removed from service.



SPECIFICATIONS

Length: 6 Ft. [1.8 m.]

ANSI Compliant: 3,600 lbs. (16kN) gated hooks.

Breaking Strength: 6,000 lbs. (2721) kg.

Materials of construction: Polyester, Steel

RELEVANT STANDARDS

Meets ANSI Z359.13.2013, OSHA 1910.140, OSHA 1926.502

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

EASE OF INSPECTION

RFID & QR CODE TAG



**ASSETS MANAGEMENT
INSPECTION APPLICATION**