

6 Ft.[1.8M.] TWIN LEG LANYARD

Internal Absorber, 4' to 6' (1.2-1.8 M.) Stretch Lanyard With Aluminum Snaphook on D-Ring End and Aluminum Rebar Hook on Anchor End.

DXFP613530

BENEFITS AND FEATURES

The Dewalt elastic stretch lanyard is designed to reduce snags and provide free movement on the jobsite. It stretches from 4 ft to 6 ft, comes with a steel and aluminum connectors, single and twin models, all with built in fall detection.

NO TANGLES: The elastic, stretch feature built into the lanyard reduces opportunity for tangles and provides ease of movement.

EASE OF INSPECTION: All DEWALT lanyards come with a QR code and RFID tag for quick scan and registration into an asset management / inspection application.

LABEL PROTECTION: ALL DEWALT Lanyards comes with a protected label pack to prevent labels from being damaged by tough conditions.

EASY FALL ALERT: All DEWALT lanyards come with an integrated impact indicator to show users when the device has seen a fall and should be removed from service.

SPECIFICATIONS

Stretch Length: 4-6 Ft. [1.6-1.8 m.]

ANSI Compliant: 3,600 lbs. (16kN) gated hooks.

Breaking Strength: 5,000 lbs. (2268) kg.

Materials of construction: Polyester, Steel

RELEVANT STANDARDS

Meets Z359.13.2013, OSHA 1910.140, OSHA 1926.502

WARNINGS

Read, understand and follow all labels and instructions prior to use.

Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

come with a istration into on. s comes from being



RFID & QR CODE TAG



ASSETS MANAGEMENT INSPECTION APPLICATION