

6 Ft. [1.8M.] TWIN LEG LANYARD

External Absorber, Tie-Back to D-Ring, Adjustable, Steel Snaphook on D-Ring End and Steel Rebar Hooks on Anchor Ends

DXFP615130

BENEFITS AND FEATURES

The DEWALT Tie-Back lanyard is perfect in situations where an anchorage point is not available. The lanyard acts as both the anchor point and connector. Available in both single and twin leg models with steel and aluminum connector options.

LIGHTWEIGHT: Small energy absorber design reduces bulk and weight.

EASE OF INSPECTION: All DEWALT lanyards come with a QR code and RFID tag for quick scan and registration into an asset management / inspection application.

LABEL PROTECTION: ALL DEWALT Lanyards comes with a protected label pack to prevent labels from being damaged by tough conditions.

EASY FALL ALERT: All DEWALT lanyards come with an integrated impact indicator to show users when the device has seen a fall and should be removed from service.



SPECIFICATIONS

Length: 6 Ft. [1.8 m.]

ANSI Compliant: 3,600 lbs. (16kN) gated hooks.

Breaking Strength: 6,000 lbs. (2721) kg.

Materials of construction: Polyester, Steel

RELEVANT STANDARDS

Meets ANSI Z359.13.2013, OSHA 1910.66, OSHA 1926.503

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY

EASE OF INSPECTION

RFID & QR CODE TAG



**ASSETS MANAGEMENT
INSPECTION APPLICATION**