

3 Ft. [0.9M.] WELDING ANCHOR STRAP

D-Ring on both ends

DXFP817003

BENEFITS AND FEATURES

The DEWALT 3 ft.(0.9m.) welding choker style web anchor strap provides a strong, durable and flexible temporary fall protection anchor solution for most welding or spark applications.

DURABILITY: Made of Aramid FR webbing for durable flame resistance, the 1-3/4 in.(4.4 cm.) Aramid FR webbing strength member provides exceptional strength and wear protection for welding applications.

COMPACT AND LIGHTWEIGHT: Weighing only .88 lbs (0.4kg.), this temporary anchor strap is easily moved and reused from location to location.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

FLEXIBILITY: Can be used as a vertical or horizontal temporary anchor point around beams, posts or other structural members.



SPECIFICATIONS

Length: 3 Ft. [0.9 m.]

Capacity: 310 lbs. (140) Kg.

Breaking Strength: 5,000 lbs. (2267) kg.

Materials of construction: Aramid FR Webbing, Steel

RELEVANT STANDARDS

Meets ANSI Z359.18-2017, OSHA 1926.502, 1910.140

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY