

# DROP THROUGH ANCHOR with 6 ft. [1.8 m] CABLE

## 6 in. [15.2 cm] Plate

### DXFP822001

#### BENEFITS AND FEATURES

The DEWALT 6 ft. (1.8m.) Reusable Drop Through Swiveling Cable Anchor is designed to be used in either steel or concrete to provide an overhead fall protection anchor point.

**DURABILITY:** The 1/4 in. (6 mm) galvanized cable provides exceptional strength and wear resistance.

**COMPACT AND LIGHTWEIGHT:** Weighing only 2.4 lbs. (1.09 kg), this temporary anchor is easily moved and reused from location to location.

**STRENGTH:** Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

**FLEXIBILITY:** Can be used as a vertical or horizontal temporary anchor point around beams, posts or other structural members.



#### SPECIFICATIONS

**Length:** 6 ft. [1.8 m]

**Breaking Strength:** 5,000 lbs. (2267 kg)

**Materials of construction:** Galvanized Cable, Polished Steel

#### RELEVANT STANDARDS

Meets ANSI Z359.18-2017, OSHA 1926.502, 1910.140

#### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

#### WARRANTY

**2 YEAR LIMITED WARRANTY**