

ANCHOR POINT

Bolt Down D-Ring - Zinc Plated

DXFP844001

BENEFITS AND FEATURES

The DEWALT Single point anchor is designed to be fixed on walls, ceilings, roof tops or steel structures. It can be used to sustain the load impact in all three axis (X, Y, & Z)

DURABILITY: The stainless steel is highly corrosion and rust resistant.

COMPACT AND LIGHTWEIGHT: At only 0.93 lbs. (0.42 kg) this anchor allows for easy installation.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23 kN) anchor point.

VERSATILITY: Can be used on a wide variety of structural members and fastened with M12 chemical or mechanical fasteners.



SPECIFICATIONS

Height: 1.5 in. (3.8 cm) **Width:** 3 in. (7.62 cm)

Capacity: 310 lbs. (140 Kg.)

Breaking Strength: 5,000 lbs. (2267) kg.

Materials of construction: Zinc Plated

RELEVANT STANDARDS

Meets ANSI Z359.18-2017 Type A, OSHA 1926.502, 1910.140

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY