

# ANCHOR POINT

## Reusable - Steel Girder

**DXFP845001**

### BENEFITS AND FEATURES

The DEWALT Steel Girder Anchor is a removable and reusable anchor point to be mounted on solid steel structures, girders and steel I-beams. It can be installed very easily with one hand and is extremely portable. The maximum thickness of the structure on which installation is possible is 1.57 in. (4 cm).

**DURABILITY:** The combination of galvanized and stainless steel provides exceptional strength, wear and corrosion resistance..

**COMPACT AND LIGHTWEIGHT:** Weighing only 1.2 lbs (0.54 kg.), this temporary anchor is easily moved and reused from location to location with one hand.

**STRENGTH:** Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.

**VERSATILITY:** Can be used as a vertical or horizontal temporary anchor point on steel structural members. Hole width of 13/16 in. (2.1cm) to 1-3/16 in. (3 cm). Material thickness up to 1-9/16 in. (4 cm).

### SPECIFICATIONS

**Length:** 4.7 in. [11.4 cm.] **Weight:** 1.21 lbs. [0.55 kg.]

**Capacity:** 310 lbs.(140 Kg.)

**Breaking Strength:** 5,000 lbs. (2267) kg.

**Materials of construction:** Alloy Steel, S. Steel Moulded Polymer

### RELEVANT STANDARDS

Meets ANSI Z359.18-2017, OSHA 1926.502, 1910.140

### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

### WARRANTY

**2 YEAR LIMITED WARRANTY**

