

BEAM ANCHOR

Sliding - Fits 3.5" (9.0 cm.) To 13.3" (34 cm.) Flange

DXFP846011

BENEFITS AND FEATURES

The DEWALT Sliding Beam Anchor is capable of being installed on the flange of horizontal beams. The variable position jaw adjustment enables it to be installed on flange widths of 3.5 in. (9.0 cm) to 13.3 in. (34 cm).

DURABILITY: The aluminum alloy and brass construction of the fixed beam anchor provides exceptional strength for a long lasting anchor point.

COMPACT AND LIGHTWEIGHT: Weighing only 4.13 lbs. (1.8 Kg.), this beam anchor is easily moved and reused from location to location.

FLEXIBILITY: Can be used as a horizontal temporary anchor point on steel beam flanges.

STRENGTH: Meets OSHA and ANSI standards of 5,000 lbs. (23kN) anchor point.



SPECIFICATIONS

Width: 3.5 in. [7.5 cm.] to : 13.3 in. [34 cm.]

Capacity: 310 lbs.(140 Kg.)

Breaking Strength: 5,000 lbs. (2267) kg.

Materials of construction: Aluminum Alloy, Brass

RELEVANT STANDARDS

Meets ANSI Z359.18-2017, OSHA 1926.502, 1910.140

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY