

# CARABINER

## Standard Self Locking Steel 1 in. (25.4 mm.) Turn

**DXFP912001**

### BENEFITS AND FEATURES

The DEWALT Quarter-Turn, Self-Locking, Bulb Style Steel Carabiner provides flexible solutions for connecting various fall protection equipment. With a 1 in (25.4 mm) gate opening, the 3,600 lb. (16kN) gate strength meets OSHA and ANSI standards for fall protection.

**FLEXIBILITY:** The large 1 in (25 mm) gate opening allows this carabiner to fit most applications.

**DURABILITY:** The galvanized alloy steel construction provides exceptional wear and weather resistance.

**STRENGTH:** Meets OSHA and ANSI standards for 3,600 lbs. (16kN) gate. Minimum breaking strength 9,000 lbs (40kN).



### SPECIFICATIONS

**Maximum Breaking Strength:** 9,000 lbs. (40 kN.)

**Capacity:** 310 lbs. (141 kg)

**Size:** 4.7 In. (119 mm.) Long, 3.28 In (83 mm.) Wide

**Weight:** 0.595 lbs. ( 270 gr.)

**Material:** Galvanized alloy steel with golden yellow/silver passivation

### RELEVANT STANDARDS

Meets ANSI Z359.12-2019, OSHA 1926.502 and 1910.140

### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

### WARRANTY

**2 YEAR LIMITED WARRANTY**