

CARABINER

Standard Self Locking Aluminum 1/4 in. (6.35 mm.) Turn

DXFP915001

BENEFITS AND FEATURES

The DEWALT Quarter-Turn, Self-Locking, Bulb Style Aluminum Carabiner provides flexible solutions for connecting various fall protection equipment. With a .83 in (21 mm) gate opening, the 3,600 lb. (16kN) gate strength meets OSHA and ANSI standards for fall protection.

FLEXIBILITY: The large 0.85 in (21.5 mm) gate opening allows this carabiner to fit most applications.

DURABILITY: The high strength aluminum alloy construction provides superior weather resistance.

STRENGTH: Meets OSHA and ANSI standards for 3,600 lbs. (16kN) gate. Minimum breaking strength 5,000 lbs (23kN).



SPECIFICATIONS

Maximum Breaking Strength: 5,000 lbs. (23 kN.)

Capacity: 310 lbs. (141 kg)

Size: 4.54 in. (115 mm.) Long, 3.07 in (78 mm.) Wide

Weight: 0.264 lbs. (120 gr.)

Material: High strength aluminum alloy

RELEVANT STANDARDS

Meets ANSI Z359.12-2019, OSHA 1926.502 and 1910.140

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

WARRANTY

2 YEAR LIMITED WARRANTY